



MANUAL SWING GATES

Features:

- Manually operated swing gates.
- Can be mounted to bollards or any solid surface.
- Standard 5 metre rail can be cut down to any length.
- Aluminium rail includes hi-viz reflective panel.
- Gate receiver for wall or post mounting included.
- Full range of round and square bollards on request.

PART No.	DESCRIPTION
MSG5000	Manual 5 metre swing gate (bollard not included)
C90SM	Surface mount round bollard – 90 x 5 x 1000mm
C90BG	Below ground round bollard – 90 x 5 x 1380mm
C140SM	Surface mount round bollard – 140 x 5 x 1200mm
C140BG	Below ground round bollard – 140 x 5 x 1700mm
MSGRK	Additional gate receiver kit

Description: Manual pedestrian or vehicle gate.

Material: Galvanised steel assembly with powder coated aluminium rail.

Finish: Powder coated Yellow with reflective.

Rail type: Aluminium extrusion 145 x 40 x 5000mm.

Operation: Push open / push close.

Gate swing: Up to 180 degrees.

Gate stop: Optional receiver post or wall receiver.

Max. open: 5 metres.

Min. open: 2 metres.

Adjustment: Rail length can be cut down on site.

Height: 1000mm.

Mounting: Can be post or wall mounted.

Weight: 35kgs gate assembly with 5 metre rail.

