



ER-RAIL

Features:

- Manufactured from extruded aluminium and powder coated Yellow.
- ER-Rails 1.75mm thick walls are light and strong.
- Optional toe boards available in two sizes.
- Available in three standard lengths or can be cut to any length with a power saw fitted with an aluminium cutting blade.
- Continuous rail lengths require fewer mounting posts thereby reducing installation time and costs.
- Designed to comply to AS 1657:2013 for balustrades and handrails when installed using ER-Rail mounting brackets.
- Can be mounted on round or square posts or wall mounted.
- Designed-in recess accommodates either 3 or 6mm sign panels or rolled-edge canvas banners.

Material:	Extruded aluminium section.
Finish:	Powder coated Yellow.
Length:	2, 3 or 6 metres.
Size:	80 x 30 with 1.75mm wall.
Weight:	1.45kgs per metre.

PART No.	DESCRIPTION
ER8030-2PA	2 metre ER-Rail with end caps — Powder coated aluminium
ER8030-3PA	3 metre ER-Rail with end caps — Powder coated aluminium
ER8030-6PA	6 metre ER-Rail with end caps — Powder coated aluminium
ERSJ20	ER-Rail connectors
ER8030-IS	2 metre ER-Rail in-fill strip — Natural anodised aluminium
ERG1200-PA	ER-Rail gate assembly (see page 30)
C63SME	Surface mount bollard — 63.5 x 1.6 x 1000mm
C63BGE	Below ground bollard – 63.5 x 1.6 x 1000mm
C90SME	Surface mount bollard — 90 x 3.2 x 1000mm
C90BGE	Below ground bollard – 90 x 3.2 x 1000mm



Wall mount model shown.



Post mount model shown.