

STYLE	PART No.	A	B	C	D	Kgs	FINISH	NC SLEEVES	E	CD SLEEVES	F
2	BCL90*	90	950	200	5	12.3	HDG+PC	BCL90S-NC	425	BCL90S-CD	225
2	BCL90-G*	90	950	200	5	12.3	HDG	BCL90S-NC	425	BCL90S-CD	225
3	BCL90-SS*	90	883	200	3.05	9	SS	BCL90SS-NC	425	BCL90SS-CD	225
4	BCL90-SSH*	90	950	200	3.05	9	SS+H	BCL90SS-NC	425	BCL90SS-CD	225
1	BCL90RD*	90	950	200	5	12.5	HDG+PC	BCL90S-NC	425	BCL90S-CD	225
1	BCL90RD-G*	90	950	200	5	12.5	HDG	BCL90S-NC	425	BCL90S-CD	225
2	BCL140*	140	1050	200	5	21	HDG+PC	BCL140S-NC	425	BCL140S-CD	225
2	BCL140-G*	140	1050	200	5	21	HDG	BCL140S-NC	425	BCL140S-CD	225
3	BCL140-SS*	140	983	200	3.4	21	SS	BCL140SS-NC	425	BCL140SS-CD	225
4	BCL140-SSH*	140	1050	200	3.4	21	SS+H	BCL140SS-NC	425	BCL140SS-CD	225
5	BHH	Wall mount bollard holder									
6	BCL90H	Cam-Lok 90mm surface mount bollard holder									
6	BCL140H	Cam-Lok 140mm surface mount bollard holder									
7	BCLKEY**	Cam-Lok additional registered key									

Note: All dimensions in mm – (A) Bollard diameter, (B) Height above ground, (C) Depth below ground, (D) Wall thickness, (E) New Concrete sleeve height, (F) Core Drilled sleeve height, Finish: Hot Dip Galvanised (HDG) only/and Powder Coated (PC), or 316 Stainless Steel (SS) only/and Aluminium cap with handle (H).

*Each order of one or more bollards is supplied with TWO registered keys.

**Additional keys are available to purchase separately.



5 Hanging holder



6 Surface mount holder



7 Additional keys