



## U-BARS Standard Duty

### Features:

- Suitable for a wide range of uses.
- Heavy 3mm thick wall tube.
- All models are galvanised and powder coated or galvanised only.
- Reflective options available.
- Surface mount and below ground models.
- Surface mount supplied with fixings.
- Supplied ready for installation with no assembly required.

**Material:** 48mm diameter steel pipe, 3mm wall.

**Finish:** Galvanised and powder coated or galvanised only.

**Height:** 800mm above ground.  
300mm below ground.

**Width:** 400 or 850mm

**Weight:** BR1 models 9.2kgs (approx.)  
BR2 models 8.5kgs (approx.)

**Installation:** 6mm thick surface flange 150mm in diameter with 8 off 10 x 50mm masonry anchors for surface mount model. Below ground model has welded concrete starter bars.

**Fixings:** Supplied with surface mount models.

PART No.	DESCRIPTION
BR1G-SM	Bike rail 850 x 800mm surface mount – Galvanised
BR1P-SM	Bike rail 850 x 800mm surface mount – Gal. & powder coat
BR1G-BG	Bike rail 850 x 1100mm below ground – Galvanised
BR1P-BG	Bike rail 850 x 1100mm below ground – Gal. & powder coat
BR2G-SM	Bike rail 400 x 800mm surface mount – Galvanised
BR2P-SM	Bike rail 400 x 800mm surface mount – Gal. & powder coat
BR2G-BG	Bike rail 400 x 1100mm below ground – Galvanised
BR2P-BG	Bike rail 400 x 1100mm below ground – Gal. & powder coat



## U-BARS Heavy Duty

### Features:

- Heavy duty 5mm thick wall.
- Three standard lengths.
- Flexible modular design.
- All models are galvanised and powder coated or galvanised only.
- Surface mount and below ground models.
- Easy on site assembly with fixings supplied.

**Material:** 90mm diameter steel pipe, 5mm wall.

**Finish:** Galvanised and powder coated or galvanised only.

**Height:** 700mm above ground.  
500mm below ground.

**Width:** 1000, 1500 or 2000mm.

**Weight:** UB100 models 31kgs (approx.)  
UB150 models 36kgs (approx.)  
UB200 models 41kgs (approx.)

**Installation:** 6mm thick surface flange 225mm in diameter with 8 off 12 x 60mm masonry anchors for surface mount model. Below ground model has welded concrete starter bars.

**Fixings:** Supplied with surface mount models. Connector pins supplied with all models.

PART No.	DESCRIPTION
UB100SM	U-Bar 1 metre surface mount (2 piece) – Gal. & powder coat
UB100SM-G	U-Bar 1 metre surface mount (2 piece) – Galvanised
UB100BG	U-Bar 1 metre below ground (2 piece) – Gal. & powder coat
UB100BG-G	U-Bar 1 metre below ground (2 piece) – Galvanised
UB150SM	U-Bar 1.5 metre surface mount (3 piece) – Gal. & powder coat
UB150SM-G	U-Bar 1.5 metre surface mount (3 piece) – Galvanised
UB150BG	U-Bar 1.5 metre below ground (3 piece) – Gal. & powder coat
UB150BG-G	U-Bar 1.5 metre below ground (3 piece) – Galvanised
UB200SM	U-Bar 2 metre surface mount (3 piece) – Gal. & powder coat
UB200SM-G	U-Bar 2 metre surface mount (3 piece) – Galvanised
UB200BG	U-Bar 2 metre below ground (3 piece) – Gal. & powder coat
UB200BG-G	U-Bar 2 metre below ground (3 piece) – Galvanised