



## De-Fence Safety Fence System

Machinery guarding and zoning system known as the De-Fence Safety Fence System. Typically installed in warehouses and factories, it provides safety guarding from active machines and pedestrian safety against moving forklifts and vehicles.

The system comprises a range of standard panel lengths with the option of welded mesh or polycarbonate infill, either single or double height.

De-fence steel posts are manufactured from 75 x 75 x 2.5mm thick RHS tube. They are pre-drilled on all four sides to accept our range of steel brackets and finished in highly visible Yellow powder coat. They are available in two standard heights with a choice of three different welded base plates.

**Designed to comply with AS 4024.1-2014 Series Safety of Machinery.**



**De-Fence Swing Gate, page 68.**



**De-Fence Sliding Gate, page 69.**



PART No.	DESCRIPTION	Fixings supplied
<b>DFP1300</b>	De-Fence standard post inline – 1300 x 75 x 75mm (10.7kgs)	
<b>DFP2460</b>	De-Fence standard post inline – 2460 x 75 x 75mm (16.5kgs)	

PART No.	DESCRIPTION	Fixings supplied
<b>DFP1300E</b>	De-Fence end post offset – 1300 x 75 x 75mm (10.7kgs)	
<b>DFP2460E</b>	De-Fence end post offset – 2460 x 75 x 75mm (17kgs)	

PART No.	DESCRIPTION	Fixings supplied
<b>DFP1300G</b>	De-Fence gate post centred – 1300 x 75 x 75mm (10.7kgs)	
<b>DFP2460G</b>	De-Fence gate post centred – 2460 x 75 x 75mm (17kgs)	



PART No.	DESCRIPTION
<b>DFP2000M</b>	De-Fence mesh infill panel – 2000mm long (18kgs)
<b>DFP1700M</b>	De-Fence mesh infill panel – 1700mm long (16kgs)
<b>DFP1500M</b>	De-Fence mesh infill panel – 1500mm long (15kgs)
<b>DFP1200M</b>	De-Fence mesh infill panel – 1200mm long (13kgs)
<b>DFP1000M</b>	De-Fence mesh infill panel – 1000mm long (10kgs)
<b>DFP750M</b>	De-Fence mesh infill panel – 750mm long (8kgs)
<b>DFP500M</b>	De-Fence mesh infill panel – 500mm long (6kgs)
<b>DF-GKP</b>	Optional gate kick plate

PART No.	DESCRIPTION
<b>DFP2000P</b>	De-Fence polycarbonate infill panel – 2000mm long (18kgs)
<b>DFP1700P</b>	De-Fence polycarbonate infill panel – 1700mm long (16kgs)
<b>DFP1500P</b>	De-Fence polycarbonate infill panel – 1500mm long (15kgs)
<b>DFP1200P</b>	De-Fence polycarbonate infill panel – 1200mm long (13kgs)
<b>DFP1000P</b>	De-Fence polycarbonate infill panel – 1000mm long (10kgs)
<b>DFP750P</b>	De-Fence polycarbonate infill panel – 750mm long (8kgs)
<b>DFP500P</b>	De-Fence polycarbonate infill panel – 500mm long (6kgs)
<b>DF-GKP</b>	Optional gate kick plate

**CUSTOM GUARDING:**

We understand that sometimes terms like 'modular' or 'standard' just don't work for every guarding application. We also understand that you may not be aware of your obligations, or where to turn for custom made machinery guarding. At Barrier Group we have the experience and the expertise to help. Call now and our consultants will come to you.



PART No.	DESCRIPTION
DF-SPB	Standard panel bracket kit



PART No.	DESCRIPTION
DF-APB	Adjustable panel bracket kit



PART No.	DESCRIPTION
DF-PCB	Panel connector bracket kit



PART No.	DESCRIPTION
DF-SGB	Self-closing gate bracket kit



PART No.	DESCRIPTION
DF-CP	De-Fence gate connector pin



PART No.	DESCRIPTION
DF-PJ	De-Fence panel joiner extrusion



PART No.	DESCRIPTION
DF-GKP	De-Fence gate kick plate



PART No.	DESCRIPTION
DF-GS	De-Fence gate stop



PART No.	DESCRIPTION
DF-LL	De-Fence lockable gate latch



PART No.	DESCRIPTION
DF-LB	De-Fence lockable drop bolt

## De-Fence Swing Gate

De-Fence self-closing mesh gates are available in either single or double height and can swing left or right. Ideal for work zoning or machinery guarding.

### Made to order:

Experience tells us that every gate application is different and requires specialist input. Call today and let us design a solution specifically for your requirements.

<b>Operation:</b>	Push open/adjustable spring closure
<b>Gate Swing:</b>	90 degrees
<b>Maximum Opening:</b>	1425mm wide
<b>Minimum Opening:</b>	925mm wide
<b>Mounting Type:</b>	Surface mounted posts
<b>Gate Type:</b>	Tubular steel frame with 3 x 25mm mesh
<b>Gate Height:</b>	1260 or 2410mm
<b>Finish:</b>	Powder coated



Note: Swing gates are available in single and double configurations

## De-Fence Sliding Gate

The sliding gate has an overhead track with a clearance of 2450mm leaving floors clear of obstacles. Available in double height only with an opening up to 2925mm wide.

### Made to order:

Experience tells us that every gate application is different and requires specialist input. Call today and let us design a solution specifically for your requirements.

<b>Operation:</b>	Manual slide open and close
<b>Gate Slide:</b>	Overhead mounted
<b>Maximum Opening:</b>	Double gates 2925mm wide
<b>Minimum Opening:</b>	Single gate 925mm wide
<b>Mounting Type:</b>	Surface mounted posts
<b>Gate Type:</b>	Tubular steel frame with 3 x 25mm mesh
<b>Gate Height:</b>	2400mm only
<b>Overhead Clearance:</b>	Floor to overhead track 2450mm
<b>Finish:</b>	Powder coated



Note: Sliding gates are available in single and double configurations