KELRYAN

# Round Bollards
## 316 Stainless Steel

Marine grade stainless steel offers a high level of performance in harsh locations, including where there will be exposure to salt air. The polished surfaces and machine finished flat caps present an aesthetically pleasing finish in architectural environments. Optional spun covers are available for surface mounted models to conceal mounting hardware.

| STYLE | PART No. | A | B | C | D | E | F | Kgs | FINISH |
|---|---|---|---|---|---|---|---|---|---|
| 1 | C90SM-SS | 90 | 900 | – | 3.05 | 6 | 225 | 7.4 | SS |
| 2 | C90BG-SS | 90 | 900 | 300 | 3.05 | – | – | 8 | SS |
| 3 | C90CD-SS | 90 | 900 | 200 | 3.05 | – | – | 7.4 | SS |
| 1 | C140SM-SS | 140 | 1200 | – | 3.4 | 10 | 300 | 19 | SS |
| 2 | C140BG-SS | 140 | 1200 | 500 | 3.4 | – | – | 25 | SS |
| 3 | C140CD-SS | 140 | 1200 | 200 | 3.4 | – | – | 22 | SS |
| 1 | C168SM-SS | 168 | 1300 | – | 3.4 | 10 | 350 | 26.5 | SS |
| 2 | C168BG-SS | 168 | 1300 | 500 | 3.4 | – | – | 31 | SS |
| 3 | C168CD-SS | 168 | 1300 | 300 | 3.4 | – | – | 29 | SS |
| + | COV90-SS | Base cover to suit 90mm bollard – 316 stainless steel (optional) | | | | | | | |
| + | COV140-SS | Base cover to suit 140mm bollard – 316 stainless steel (optional) | | | | | | | |
| + | COV168-SS | Base cover to suit 168mm bollard – 316 stainless steel (optional) | | | | | | | |
| + | RKIT-SS | Stainless steel chain ring kit 2 x M10 eye bolts | | | | | | | |
| + | SSC6 | Stainless steel chain per metre | | | | | | | |

**Note:** All dimensions in mm – **(A)** Bollard diameter, **(B)** Height above ground, **(C)** Depth below ground, **(D)** Wall thickness, **(E)** Base plate thickness, **(F)** Base plate diameter.
**Finish:** 316 Stainless Steel (SS).

Copyright © 2019 Kelryan Group Pty. Ltd.