

STYLE	PART No.	A	B	C	D	Kgs	FINISH	NC SLEEVES	E	CD SLEEVES	F
2	BSL63	63	900	150	1.6	4.5	HDG+PC	BSL63S-NC	300	BSL63S-CD	150
2	BSL63-G	63	900	150	1.6	4.5	HDG	BSL63S-NC	300	BSL63S-CD	150
2	BSL90	90	950	200	5	12	HDG+PC	BSL90S-NC	425	BSL90S-CD	225
2	BSL90-G	90	950	200	5	12	HDG	BSL90S-NC	425	BSL90S-CD	225
3	BSL90-SS	90	883	200	3.05	9	SS	BSL90SS-NC	425	BSL90SS-CD	225
4	BSL90-SSH	90	950	200	3.05	9	SS+H	BSL90SS-NC	425	BSL90SS-CD	225
1	BSL90RD	90	950	200	5	12.2	HDG+PC	BSL90S-NC	425	BSL90S-CD	225
1	BSL90RD-G	90	950	200	5	12.2	HDG	BSL90S-NC	425	BSL90S-CD	225
2	BSL140	140	1050	200	5	21	HDG+PC	BSL140S-NC	425	BSL140S-CD	225
2	BSL140-G	140	1050	200	5	21	HDG	BSL140S-NC	425	BSL140S-CD	225
3	BSL140-SS	140	983	200	3.4	21	SS	BSL140SS-NC	425	BSL140SS-CD	225
4	BSL140-SSH	140	1050	200	3.4	21	SS+H	BSL140SS-NC	425	BSL140SS-CD	225
5	BHH	Wall mount bollard holder									
6	BSL63H	Sleeve-Lok 63mm surface mount bollard holder									
6	BSL90H	Sleeve-Lok 90mm surface mount bollard holder									
6	BSL140H	Sleeve-Lok 140mm surface mount bollard holder									
7	BPL2	High security 9mm shielded padlock with 2 keys									

Note: All dimensions in mm – (A) Bollard diameter, (B) Height above ground, (C) Depth below ground, (D) Wall thickness, (E) New Concrete sleeve height, (F) Core Drilled sleeve height. **Finish:** Hot Dip Galvanised (HDG) only/and Powder Coated (PC), or 316 Stainless Steel (SS) only/and Aluminium cap with handle (H).



5 Hanging holder



6 Surface mount holder



7 BPL2 high security shielded padlock