

KELRYAN



Retractable Bollards

Retractable bollards are designed for medium security applications such as traffic and parking control.

They offer a simple, trouble-free operation proven over many years of installation. The KBR900 has a 5mm thick mild steel bollard that is galvanised before being powder coated in Hi-vis Yellow with two Red reflective bands. The KBR900-G is a hot dip galvanised 5mm thick mild steel bollard.

The KBR900-SS has a 316 marine grade stainless steel bollard with a 3.05mm thick wall, and as this model is designed for architectural applications it does not include reflective bands.

STYLE	PART No.	A	B	C	D	E	F	G	FINISH
1	KBR900*	90	900	1150	5	140	41.5	12.5	HDG+PC
2	KBR900-G	90	900	1150	5	140	41.5	12.5	HDG
3	KBR900-SS*	90	900	1150	3.05	140	38	8.8	SS
4	KBR900R	Replacement bollard for BR900							
5	KBR900R-G	Replacement bollard for BR900-G							
6	KBR900R-SS	Replacement bollard for BR900-SS							
7	KBRKEY-P**	Additional T-handle key							

Note: All dimensions in mm – (A) Bollard diameter, (B) Height above ground, (C) Depth below ground, (D) Wall thickness, (E) In-ground casing diameter, (F) Shipping weight (Kgs), (G) Operating weight (Kgs). Finish: Hot Dip Galvanised (HDG), Powder Coated (PC), or 316 Stainless Steel (SS).

*Each order of one or more bollards is supplied with TWO T-handle keys.

**Additional keys are available to purchase separately.

