

COMPATIBLE SYSTEMS



Recess mounted
11 mm thick



Wall mounted
24 mm thick



Video intercom
version



7" display



5-inch display



Version for the
hearing impaired



Speaker audio

Do you want a design product full of technology? Choose XTS.

This is the new range of video entry panel systems, available with 7 and 5-inch monitors - fully touch screen. The minimal design and quality of the materials exalt its elegance, whether you choose the white or black version. The high-resolution glass screen with Optical Bonding technology ensures perfect viewing in all lighting conditions. Having WiFi, both in the X1 and IP versions, makes it the choice for managing the video intercom system and opening the front door from a smartphone.

PLUS

Full-duplex speaker audio

Capacitive touch screen

Display with Optical Bonding anti-glare technology

Auxiliary/porter calls functions

Intercom calls

"Panic" key for emergency calls to the porter

Adjust/exclude ringtone (with alert LED when excluded)

Self-inserting video from entry panels

Video answering service and video recording

Local or POE power supply

AVAILABLE VERSIONS




Recess mounted



Wall mounted

DIMENSIONS (MM)





PLUS

- Full-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings.
- RJ45 port for directly connecting to the Ethernet
- On-board WiFi for remotely controlling calls
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Up to 19 mobile devices for managing the system from any remote location
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited intercom calls to other receivers and mobile devices
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Send and receive text messages to and from the porter or other monitor extensions
- Live feeds of the connected IP video cameras
- Automatic opening function during business hours
- Standard SIP protocol, codec video H.264, codec audio G711
- On-board web server for configuring and managing via the browser



XTS 7IP WH WIFI
840CH-0060

TECHNICAL CHARACTERISTICS

MODELS	XTS 7IP WH WIFI
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
PoE power supply	IEEE 802.3af-PD
Consumption in stand-by mode (mA)	340
Max. absorption (mA)	420
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	H.264
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	White

CODE DESCRIPTION

XTS 7IP WH WIFI
840CH-0060

Full touch speaker video intercom for IP360 system, 7" TFT touch-screen display, WiFi and Graphical User Interface - white.

Wall monitor with 7" TFT touch screen display with Moth-Eye technology, integrated Wi-Fi for the remote operation of calls on smartphone with dedicated app. User interface for management of the functions of video entry phone, intercom calls, video recording, text messages. It uses the SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network connection, PoE or local power supply. Integrated web service for configuration and firmware updates. A bracket is included for wall installation on 503 box (horizontal or vertical) and on round box Ø 60 mm. Suitable for built-in installation with dedicated box. Compatible with IP360 systems.





PLUS

- Full-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings.
- RJ45 port for directly connecting to the Ethernet
- On-board WiFi for remotely controlling calls
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Up to 19 mobile devices for managing the system from any remote location
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited intercom calls to other receivers and mobile devices
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Send and receive text messages to and from the porter or other monitor extensions
- Live feeds of the connected IP video cameras
- Automatic opening function during business hours
- Standard SIP protocol, codec video H.264, codec audio G711
- On-board web server for configuring and managing via the browser

XTS 7IP BK WIFI 840CH-0070

TECHNICAL CHARACTERISTICS

MODELS	XTS 7IP BK WIFI
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
PoE power supply	IEEE 802.3af-PD
Consumption in stand-by mode (mA)	340
Max. absorption (mA)	420
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	H.264
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	Black

CODE	DESCRIPTION
------	-------------

**XTS 7IP BK WIFI
840CH-0070**

Full-touch speaker video intercom for IP360 system, 7" TFT touch screen display, Wi-Fi and Graphical User Interface - black.

Wall monitor with 7" TFT touch screen display with Moth-Eye technology, integrated Wi-Fi for the remote operation of calls on smartphone with dedicated app. User interface for management of the functions of video entry phone, intercom calls, video recording, text messages. It uses the SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network connection, PoE or local power supply. Integrated web service for configuration and firmware updates. A bracket is included for wall installation on 503 box (horizontal or vertical) and on round box Ø 60 mm. Suitable for built-in installation with dedicated box. Compatible with IP360 systems.





PLUS

- Full-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings.
- RJ45 port for directly connecting to the Ethernet
- On-board WiFi for remotely controlling calls
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Up to 19 mobile devices for managing the system from any remote location
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited intercom calls to other receivers and mobile devices
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Send and receive text messages to and from the porter or other monitor extensions
- Live feeds of the connected IP video cameras
- Automatic opening function during business hours
- Standard SIP protocol, codec video H.264, codec audio G711
- On-board web server for configuring and managing via the browser
- Suitable for hearing aid users



XTS 7IP WH WFBF
840CH-0080

TECHNICAL CHARACTERISTICS

MODELS	XTS 7IP WH WFBF
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
PoE power supply	IEEE 802.3af-PD
Consumption in stand-by mode (mA)	340
Max. absorption (mA)	420
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	H.264
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	White

CODE DESCRIPTION

XTS 7IP WH WFBF 840CH-0080 Full-touch speaker video intercom for IP360 system, 7" TFT touch screen display, Wi-Fi and Graphical User Interface - white.

Wall monitor with 7" TFT touch screen display with Moth-Eye technology, integrated Wi-Fi for the remote operation of calls on smartphone with dedicated app. User interface for management of the functions of video entry phone, intercom calls, video recording, text messages. It uses the SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network connection, PoE or local power supply. Integrated web service for configuration and firmware updates. It integrates an audio frequency induction system for hearing aids in "T" position. A bracket is included for wall installation on 503 box (horizontal or vertical) and on round box Ø 60 mm. Suitable for built-in installation with dedicated box. Compatible with IP360 systems.





PLUS

- Full-duplex speaker audio
- 5" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- RJ45 port for directly connecting to the Ethernet
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different melodies for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Send and receive text messages to and from the porter or other monitor extensions
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, codec video H.264, codec audio G711
- On-board web server for configuring and managing via the browser

XTS 5IP WH 840CH-0090

TECHNICAL CHARACTERISTICS


MODELS	XTS 5IP WH
Dimensions (mm)	138 X 98 X 24
Local power supply (V)	14 ÷ 18 DC
PoE power supply	IEEE 802.3af-PD
Consumption in stand-by mode (mA)	270
Max. absorption (mA)	330
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	H.264
Frequency (MHz)	
Wireless Standard	
Color	White

CODE	DESCRIPTION
------	-------------

**XTS 5IP WH
840CH-0090**

Full-touch speaker video intercom for IP360 system, 5" TFT touch screen display, with Graphical User Interface - white.

Wall monitor with 5" TFT touch screen display with Moth-Eye technology. User interface for management of the functions of video entry phone, intercom calls, video recording, text messages. It uses the SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network connection, PoE or local power supply. Integrated web service for configuration and firmware updates. A bracket is included for wall installation on 503 box (horizontal or vertical) and on round box Ø 60 mm. Suitable for built-in installation with dedicated box. Compatible with IP360 systems.





PLUS

- Full-duplex speaker audio
- 5" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings.
- RJ45 port for directly connecting to the Ethernet
- Local or PoE (Powered over Ethernet) power supply
- Customizable user interface with UI Creator software
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different melodies for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Send and receive text messages to and from the porter or other monitor extensions
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, codec video H.264, codec audio G711
- On-board web server for configuring and managing via the browser



XTS 5IP BK 840CH-0100

TECHNICAL CHARACTERISTICS

MODELS	XTS 5IP BK
Dimensions (mm)	138 X 98 X 24
Local power supply (V)	14 ÷ 18 DC
PoE power supply	IEEE 802.3af-PD
Consumption in stand-by mode (mA)	270
Max. absorption (mA)	330
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	H.264
Frequency (MHz)	
Wireless Standard	
Color	Black

CODE	DESCRIPTION
------	-------------

**XTS 5IP BK
840CH-0100**

Full-touch speaker video intercom for IP360 system, 5" TFT touch screen display, with Graphical User Interface - black.

Wall monitor with 5" TFT touch screen display with Moth-Eye technology. User interface for management of the functions of video entry phone, intercom calls, video recording, text messages. It uses the SIP protocol and G711 audio codec and H.264 video codec. RJ45 port for network connection, PoE or local power supply. Integrated web service for configuration and firmware updates. A bracket is included for wall installation on 503 box (horizontal or vertical) and on round box Ø 60 mm. Suitable for built-in installation with dedicated box. Compatible with IP360 systems.





PLUS

- Half-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- On-board WiFi for remotely controlling calls over smartphones and tablets running the specific App
- Local power supply 14 -18 VDC
- Up to 4 mobile device for managing the system from any remote location
- Configurable quick controls: main entrance door-opener, auxiliary command
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different melodies for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Intercom calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, codec video H.264, codec audio G711
- On-board web server for configuring and managing via the browser

XTS 7 WH WIFI 840CH-0030

TECHNICAL CHARACTERISTICS

MODELS	XTS 7 WH WIFI
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
Local absorption (mA)	520
Consumption in stand-by mode (mA)	360
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	PAL/NTSC
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	White

CODE	DESCRIPTION
------	-------------

**XTS 7 WH WIFI
840CH-0030**

Full-touch speaker video intercom for X1 system, 7" TFT touch screen display, Wi-Fi and Graphical User Interface - white.

Wall monitor with 7" TFT touch screen display with Moth-Eye technology, integrated Wi-Fi for the remote operation of calls on smartphone with dedicated app. User interface for management of the functions of video entry phone, intercom calls, video recording. It uses the SIP protocol and G711 audio codec and H.264 video codec. 14-18 VDC local power supply. Integrated web service for configuration and firmware updates. A bracket is included for wall installation on 503 box (horizontal or vertical) and on round box Ø 60 mm. Suitable for built-in installation with dedicated box. Compatible with X1 and XIP systems.





PLUS

- Half-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- On-board WiFi for remotely controlling calls
- Local power supply 14 -18 V DC
- Up to 4 connectable mobile devices per unit
- Configurable quick controls (default main entrance door-opener)
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Unlimited intercom calls to other receivers and mobile devices
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Live feeds of the connected IP video cameras
- Automatic opening function during business hours
- Standard SIP protocol, codec video H.264, codec audio G711
- On-board web server for configuring and managing via the browser



XTS 7 BK WIFI
840CH-0040

TECHNICAL CHARACTERISTICS

MODELS	XTS 7 BK WIFI
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
Local absorption (mA)	520
Consumption in stand-by mode (mA)	360
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	PAL/NTSC
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	Black

CODE DESCRIPTION

XTS 7 BK WIFI
840CH-0040

Full-touch speaker video intercom for X1 system, 7" TFT touch screen display, Wi-Fi and Graphical User Interface - black.

Wall monitor with 7" TFT touch screen display with Moth-Eye technology, integrated Wi-Fi for the remote operation of calls on smartphone with dedicated app. User interface for management of the functions of video entry phone, intercom calls, video recording. It uses the SIP protocol and G711 audio codec and H.264 video codec. 14-18 VDC local power supply. Integrated web service for configuration and firmware updates. A bracket is included for wall installation on 503 box (horizontal or vertical) and on round box Ø 60 mm. Suitable for built-in installation with dedicated box. Compatible with X1 and XIP systems.





PLUS

- Suitable for hearing aid users
- Half-duplex speaker audio
- 7" TFT display Full touch-screen with Optical Bonding anti-glare technology for enhanced readability in brightly lit settings
- On-board WiFi for remotely controlling calls over smartphones and tablets running the specific App
- Local power supply 14 -18 VDC
- Up to 4 mobile device for managing the system from any remote location
- Configurable quick controls: main entrance door-opener, auxiliary command
- List of AUX commands for activating auxiliary functions
- "Panic" function for emergency calls to the porter (if present on the system)
- Audio video settings: ringtone volume, display brightness, interface backgrounds
- Different melodies for entry panels and landings
- Exclude ringtone key (the alert LED lights up when silenced)
- Self-inserting video of entry panels with cyclic selection
- Intercom calls to other receivers and smartphones and tablets
- Contacts list and favorites list
- Video answering service, stores up to 100, 10-second audio and video messages.
- Audio and video recording during conversations
- Live feeds of the connected IP video cameras
- Business function: for automatic door opening during business hours
- Block display function for cleaning
- Standard SIP protocol, codec video H.264, codec audio G711
- On-board web server for configuring and managing via the browser

XTS 7 WH WFBF 840CH-0050

TECHNICAL CHARACTERISTICS

MODELS	XTS 7 WH WFBF
Dimensions (mm)	185 x 129 x 24
Local power supply (V)	14 ÷ 18 DC
Local absorption (mA)	520
Consumption in stand-by mode (mA)	360
Operating temperature (°C)	0 ÷ +40
Protection rating (IP)	30
Video standard	PAL/NTSC
Frequency (MHz)	2.412 - 2.472
Wireless Standard	IEEE 802.11b/g/n
Color	White

CODE	DESCRIPTION
------	-------------




**XTS 7 WH WFBF
840CH-0050**

Full-touch speaker video intercom for X1 system, 7" TFT touch screen display, Wi-Fi and Graphical User Interface, on-board teleloop - white.

Wall monitor with 7" TFT touch screen display with Moth-Eye technology, integrated Wi-Fi for the remote operation of calls on smartphone with dedicated app. User interface for management of the functions of video entry phone, intercom calls, video recording. It uses the SIP protocol and G711 audio codec and H.264 video codec. 14-18 VDC local power supply. Integrated web service for configuration and firmware updates. It integrates an audio frequency induction system for hearing aids in "T" position. A bracket is included for wall installation on 503 box (horizontal) and on round box Ø 60 mm. Suitable for built-in installation with dedicated box. Compatible with X1 and XIP systems.



Accessories

CODE	DESCRIPTION	
XTS 7SI 840XC-0080	Recess-mounting box for XTS 7 entry panels. Plastic recess-mounting box with pre-punched holes for passing the cables, complete with mortar protection.	
XTS 5SI 840XC-0090	Recess-mounting box for XTS 5 entry panels. Plastic recess-mounting box with pre-punched holes for passing the cables, complete with mortar protection.	
XTS 7SIC 840XC-0100	Recess-mounting box for plasterboard walls for XTS 7 entry panels. Plastic recess-mounting box with pre-punched holes for passing cables, ideal for plasterboard walls of up to 22 mm in thickness.	
XTS 5SIC 840XC-0110	Recess-mounting box for plasterboard walls for XTS 5 entry panels. Plastic recess-mounting box with pre-punched holes for passing cables, ideal for plasterboard walls of up to 22 mm in thickness.	
XTS 7KT 840XC-0120	Desktop stand for XTS 7 entry panels. Plexiglass 10 mm-thick stand, supplied with white 3 m CAT5 cable and terminal board cover with PMMA laminate - metallic gray.	
XTS 5KT 840XC-0130	Desktop stand for XTS 5 entry panels. Plexiglass 10 mm-thick stand, supplied with white 3 m CAT5 cable and terminal board cover with PMMA laminate - metallic gray.	