

# KELRYAN

## Galvanised Hoop Bollards Heavy Duty Steel

Hoop Bollards are rolled from a single piece of heavy wall pipe and are available at either 600 or 900mm wide models (500 or 810mm post centre to centre). Choose from three mounting options; fixed surface mount, fixed in-ground or removable in-ground. For removable models, there are two in-ground lockable sleeve options; Core Drilled (for existing concrete) or New Concrete. Hot dip galvanised is the standard finish but they can be powder coated in various colours on request (charges will apply).

STYLE	PART No.	A	B	C	D	E	F	G	CLR	Kgs	FINISH
1	CH9050SM-G	90	600	1100	-	5	225	6	250	31.4	HDG
2	CH9050BG-G	90	600	1100	300	5	-	-	250	28	HDG
3	CH9050SL-G	90	600	1100	225	5	-	-	250	29	HDG
4	CH9081SM-G	90	900	1100	-	5	225	6	405	29.8	HDG
5	CH9081BG-G	90	900	1100	300	5	-	-	405	33.2	HDG
6	CH9081SL-G	90	900	1100	225	5	-	-	405	31.2	HDG
7	BSL90S-NC	New concrete sleeve for 90mm hoop bollard – 2 required									
8	BSL90S-CD	Core drilled sleeve for 90mm hoop bollard – 2 required									
9	BPL2	High security 9mm shielded padlock with 2 keys									

**Note:** All dimensions in mm – (A) Post diameter, (B) Overall unit width, (C) Height above ground, (D) Depth below ground, (E) Wall thickness, (F) Base plate diameter, (G) Base plate thickness, (CLR) Centreline radius. **Finish:** Hot Dip Galvanised (HDG).

